

DIGITUS DIGITUS серверный шкаф серии Unique - 800 мм x 1000 мм (ШхГ)

DN-19 SRV-26U-8-N-1
EAN 4016032368397



26U server rack, Unique, 1260x800x1000 mm perforated steel doors, color grey (RAL 7035)

The server cabinets from the Unique series were developed for especially convenient and flexible network cabling. Inlets to the side in the roof and floor equipped with brushes (starting with a cabinet width of 800 mm), a sliding inlet with foam rubber seal as well as an additional rear brush inlet in the floor structure, enable versatile use in a wide range of application scenarios. Single perforated front doors and double perforated back doors, including swing handle with profile half-cylinder, ensure improved air circulation. The roof is equipped with a perforated cover for improved air circulation. This features a special design for easy mounting of a fan module. Two pairs of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth is adjustable and they are connected to additional depth bars in the cabinet. Each cabinet is made of up to 2.0 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Side walls and doors that can be locked or removed in a modular design (horizontally separated starting from 42 rack units) improve accessibility. The door hinges can be switched. Furthermore, the cabinets can be completely dismantled if necessary due to their collapsible design.

- Класс защиты IP20
- Двойные задние двери
- Двойные задние двери

- Профильные направляющие 483 мм (19") регулируются по глубине установки и имеют маркировку высоты в монтажных единицах
- Встроенные опорные балки обеспечивают устойчивость
- Встроенные опорные балки обеспечивают устойчивость
- Шкаф оснащен различными точками заземления для встроенных компонентов
- Шкаф оснащен различными точками заземления для встроенных компонентов
- Поставляется в сборе
- Cabinet type: Server cabinet
- Color: light grey, RAL 7035
- Depth: 1000 mm
- Front door: Steel door, perforated, single opening
- Load capacity: 1000 kg
- Rear door: Steel door, perforated, double opening
- Side panels: Both sides
- Units: 26
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes

Package contents

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- Installation Kit for Profile Half Cylinder
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	82.00	128.00	88.00	140.00	1,576,960.00
Packaging Unit Inside	1	82.00	128.00	88.00	140.00	1,576,960.00
Packaging Unit Single	1	82.00	128.00	88.00	140.00	1,576,960.00
Net single without Packaging	1	75.00	100.00	80.00	126.00	0.00