


DIGITUS® Cisco-compatible mini GBIC (SFP) Module, 1.25 Gbps, 0.55km

DN-81000-02

EAN 4016032369943



1.25 Gbps SFP Module, Multimode, Cisco-compatible LC Duplex Connector, 850nm, up to 550m, Cisco

Digitus® Mini GBIC (SFP) is a Cisco-compatible SFP module that provides 1.25 Gbps multimode transmission over 50/125µm OM3 multimode fiber. It is designed for use in Cisco switches and routers. The module is plug-and-play and supports a wide range of temperatures.

Plug and Play

- Digitus Mini GBIC SFP (Cisco-compatible SFP)
- Multimode transmission over 50/125µm OM3 multimode fiber
- Transmission rate: 1.25 Gbps
- Compliant with IEEE 802.3z
- Compliant with EN 60825-1
- Plug and Play
- Supports MSA (Cisco, Universal)
- Connector: LC
- 1000Base-SX – 850 nm
- Operating temperature: 0-70 °C

- Operating temperature: 0-70 °C
- Distance: 0.55 km
- Wavelength: 850 nm
- Ethernet speed: Gigabit

Attributes

- Mode: Multimode
- Connector: LC
- Distance (km): 0.5
- Wavelength: 850 nm
- DDM Support: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco, Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- 1 SFP

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	3.10	11.80	9.00	329.22
Net single without Packaging	1	0.02	1.00	5.90	0.80	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com