

DIGITUS® HP-compatible SFP+ 10G SM 1310nm 10km with DDM

DN-81201-01

EAN 4016032370031



10G SFP+ Module, Singlemode, DDM, HP-compatible LC Duplex Connector, 1310nm, up to 10km, HP

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex

- Wavelength: 1310nm
- Transmission Power: Minimum -8 dBm, Maximum -0,5 dBm
- Sensitivity Receiving Power: Minimum -12.5 dBm
- For a distance of up to 10,0km
- Safe fast-locking mechanism
- Operating temperature: 0 °C ~ 70 °C
- HP compatible
- HP-Aruba compatible

Attributes

- Mode: Singlemode
- Connector: LC
- Distance (km): 10
- Wavelength: 1310 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: HP
- Ethernet speed: 10 Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	2.00	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.10	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.10	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

More images:



Part Number	Rate	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Model
Fast Ethernet							
DS-4940	10/100/1000	10/100	10km	LC	1310nm	0 to 70 °C	
DS-4941	10/100/1000	10/100	10km	LC	1550nm	0 to 70 °C	
DS-4942	10/100/1000	10/100	10km	LC	1310nm	0 to 70 °C	
10G							
DS-4943	10/100/1000	10/100	10km	LC	1310nm	0 to 70 °C	
DS-4944	10/100/1000	10/100	10km	LC	1550nm	0 to 70 °C	
DS-4945	10/100/1000	10/100	10km	LC	1310nm	0 to 70 °C	
DS-4946	10/100/1000	10/100	10km	LC	1550nm	0 to 70 °C	
DS-4947	10/100/1000	10/100	10km	LC	1310nm	0 to 70 °C	
DS-4948	10/100/1000	10/100	10km	LC	1550nm	0 to 70 °C	
DS-4949	10/100/1000	10/100	10km	LC	1310nm	0 to 70 °C	
DS-4950	10/100/1000	10/100	10km	LC	1550nm	0 to 70 °C	
10G Industrial Model							
DS-4951	10/100/1000	10/100	10km	LC	1310nm	-40 to 85 °C	✓
DS-4952	10/100/1000	10/100	10km	LC	1550nm	-40 to 85 °C	✓
DS-4953	10/100/1000	10/100	10km	LC	1310nm	-40 to 85 °C	✓
DS-4954	10/100/1000	10/100	10km	LC	1550nm	-40 to 85 °C	✓
DS-4955	10/100/1000	10/100	10km	LC	1310nm	-40 to 85 °C	✓
DS-4956	10/100/1000	10/100	10km	LC	1550nm	-40 to 85 °C	✓

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com