

DIGITUS HP-compatible SFP+ 10G SM 1310nm 10km with DDM

DN-81201-01
EAN 4016032370031



10G SFP+ Module, Singlemode, DDM, HP-compatible LC Duplex Connector, 1310nm, up to 10km, HP

Модули трансиверов DIGITUS® Mini GBIC (SFP) обеспечивают наивысшее качество и надежность. Будь то соединение между коммутаторами, между конвертером и коммутатором, между конвертерами или другие, обширные возможности применения: Большое разнообразие модулей DIGITUS® позволяет гибко использовать технологию стекловолокна. Благодаря соответствию стандарту MSA (Multi Source Agreement) обеспечивается совместимость с о сторонними производителями.

Стекловолоконное соединение Plug and Play

- Модуль Mini GBIC SFP (компактный приёмопередатчик)
- Поддерживает DDM (Digital Diagnostic Monitoring)
- Высокое качество и максимальная отказоустойчивость
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Класс 1 лазерный продукт по EN 60825-1
- Простая установка Plug and Play
- Совместим со стандартом MSA (сетевое соглашение)

- С возможностью оперативной замены
- Тип подключения: 1 дуплекс LC
- Длина волны: 1310 нм
- Мощность передатчика: не менее -8 дБм, макс. -0,5 дБм
- Чувствительность приемника, не менее -12.5 дБм
- Для расстояния до 10 км
- Надежный быстродействующий механизм
- Рабочая температура: 0-70 °C

Attributes

- Mode: Singlemode
- Connector: LC
- Distance (km): 10
- Wavelength: 1310 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: HP
- Ethernet speed: 10 Gigabit

Package contents

- Модуль SFP

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	2.00	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.10	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.10	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

More images:



Part Number	Rate	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Model
SFP Modules							
Fast Ethernet							
DS-4910	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4911	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4912	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4913	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4914	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4915	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4916	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4917	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4918	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4919	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4920	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4921	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4922	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4923	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4924	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4925	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4926	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4927	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4928	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4929	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4930	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4931	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4932	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4933	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4934	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4935	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4936	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4937	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4938	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4939	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4940	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4941	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4942	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4943	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4944	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4945	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4946	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4947	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4948	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4949	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4950	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4951	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4952	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4953	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4954	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4955	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4956	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4957	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4958	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4959	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4960	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4961	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4962	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4963	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4964	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4965	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4966	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4967	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4968	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4969	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4970	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4971	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4972	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4973	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4974	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4975	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4976	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4977	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4978	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4979	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4980	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4981	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4982	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4983	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4984	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4985	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4986	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4987	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4988	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4989	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4990	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4991	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4992	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4993	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4994	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4995	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4996	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4997	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓
DS-4998	10/100	10/100 Mbps	10 km	LC-Multimode Duplex	19mm	0 to 70 °C	✓
DS-4999	10/100	10/100 Mbps	10 km	LC-BiDi Multimode Duplex	19mm	0 to 70 °C	✓

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com