

DIGITUS® Network cabinet Unique series - 800x1000 mm (WxD)

DN-19 26U-8/10-B-1
 EAN 4016032370789



26U network rack, Unique 1342x800x1000 mm, color black (RAL 9005)

The DIGITUS Unique series network cabinet is designed for high-density server and network equipment. It features a robust steel construction and a glass front door for easy access to the internal components. The cabinet is available in a standard black finish (RAL 9005) and is suitable for indoor use in a clean, dry environment.

The DIGITUS Unique series network cabinet is designed for high-density server and network equipment. It features a robust steel construction and a glass front door for easy access to the internal components. The cabinet is available in a standard black finish (RAL 9005) and is suitable for indoor use in a clean, dry environment.

- Protection class: IP20
 - Depth: 1000 mm
 - Front door: Glass door, single opening
 - Load capacity: 1200 kg
 - Rear door: Steel door and cable entry, double opening
 - Side panels: Both sides
 - Units: 26
 - Width: 800 mm
 - IP protection class: IP20
 - Mounted: yes
- Package contents**
- Earthing cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|--------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 1 | 89.00 | 105.00 | 85.00 | 139.20 | 1,242,360.00 |
| Packaging Unit Inside | 1 | 89.00 | 105.00 | 85.00 | 139.20 | 1,242,360.00 |
| Packaging Unit Single | 1 | 89.00 | 105.00 | 85.00 | 139.20 | 1,242,360.00 |
| Net single without Packaging | 1 | 0.00 | 100.00 | 80.00 | 134.20 | 0.00 |

Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.

- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com