

# DIGITUS® 2x2x2x2-2x2x2 CAT 6 U-UTP

DK-1612-020/Y

EAN 4016032371977



### CAT 6, U-UTP patch cord, PVC AWG 26/7, length 2 m, color yellow

Digitus® CAT 6. 250 MHz, 100 Ohm, 4x2 AWG 26/7, twisted pair, U-UTP, unshielded, PVC jacket, yellow, length 2 m, RJ45 (8P8C) connectors. Category: CAT 6

- 2 RJ45 (8P8C)
- 250 MHz, 100 Ohm, 4x2 AWG 26/7, twisted pair, U-UTP, unshielded, PVC jacket, yellow, length 2 m, RJ45 (8P8C) connectors
- 250 MHz, 100 Ohm, 4x2 AWG 26/7, twisted pair, U-UTP, unshielded, PVC jacket, yellow, length 2 m, RJ45 (8P8C) connectors





#### Attributes

- Assortment: Twisted Pair Patch Cables

- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DigiTUS PolyPkg
- Category: CAT 6
- Shielding: U-UTP, unshielded
- Length: 2 m
- Color: yellow
- Jacket: PVC
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair
- Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	150	8.50	36.00	36.00	27.00	34,992.00
Packaging Unit Inside	10	0.57	6.00	25.00	42.00	6,300.00
Packaging Unit Single	1	0.06	1.20	14.00	25.00	420.00
Net single without Packaging	1	0.05	1.10	1.20	1.30	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)