

# DIGITUS® DIGITUS Unique - 600 x 1000

DN-19 26U-6/10-B-1  
EAN 4016032377962



## 26U network rack, Unique 1342x600x1000 mm, color black (RAL 9005)

The DIGITUS Unique 26U network rack is a high-quality, industrial-grade server cabinet. It features a robust steel construction and a sleek black finish (RAL 9005). The cabinet is designed for easy installation and maintenance, with a front glass door and a rear steel door. It is suitable for use in a variety of environments, including data centers and server rooms.

The DIGITUS Unique 26U network rack is a high-quality, industrial-grade server cabinet. It features a robust steel construction and a sleek black finish (RAL 9005). The cabinet is designed for easy installation and maintenance, with a front glass door and a rear steel door. It is suitable for use in a variety of environments, including data centers and server rooms.

- Protection class: IP20
- Front door: Glass door, single opening
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 26
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes
- Package contents
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	78.00	105.00	65.00	139.20	950,040.00
Packaging Unit Inside	1	78.00	105.00	65.00	139.20	950,040.00
Packaging Unit Single	1	78.00	105.00	65.00	139.20	950,040.00
Net single without Packaging	1	77.00	100.00	60.00	134.20	0.00

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)