

# DIGITUS® Internal power supply cable

AK-430405-003-M  
EAN 4016032382140



## Internal Y-power supply cable M/F/F, 0.3m, SATA 15-pin - 2x SATA 15-pin

This cable used for the power distribution of 2 SATA-HDD's over one SATA 15-pin port of the PC power supply.

### Safe connection and power supply

- SATA 15-pin, plug <=> 2x SATA 15-pin, jack

### Attributes

- Asortiman: Unutarnji kabeli za napajanje

- AWG: 18
- Kabel u boji: razno
- Kapice: plastično
- Konektor 1: SATA, 15-polni utikač
- Konektor 2: 2x SATA, 15-polni priključak
- Konektor u boji: crni
- Materijal žice: CU
- Duljina: 0.3 m
- oklop: bez oklopa

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
<b>Packaging Unit Carton</b>	250	10.00	35.00	26.00	24.00	21,840.00
<b>Packaging Unit Inside</b>	10	0.40	28.00	18.00	4.00	2,016.00
<b>Packaging Unit Single</b>	1	0.04	19.50	10.00	1.00	195.00
<b>Net single without Packaging</b>	1	0.02	105.00	8.00	1.00	0.00

## Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)