


DIGITUS® Wall Mounting Cabinets - Slim

DN-19 WM-3H3V-SL
EAN 4016032383116



Wall mounting cabinet, slim, 900x600x200 mm 3U horizontal and 3U vertical, grey (RAL 7035)

The 483 mm (19") wall mounting cabinets of the slim series allow a horizontal or vertical mounting of 3U with two independent mounting areas for patch panels, switches, routers or other 483 mm (19") active components.

Slim design with rotating mounting profiles inside

- 1.0 - 1.5 mm strong steel sheet
- 2x 3U usable mounting areas
- Mounting areas can be turned by 100°
- Punched out cable entries with plastic cover on all sides (145x70 mm)
- Bottom is prepared for fan units
- Lockable front door with air ventilation slots
- Several cable fixing points for a neat cable management
- Maximum equipment mounting height inside (from top profile to base): 650 mm

Attributes

- Cabinet type: Wall mounting cabinet, home automation
- Color: light grey, RAL 7035
- Depth: 200 mm
- Front door: Steel door, closed, single opening
- Load capacity: 100 kg
- Side panels: Both sides
- Units: 3
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

Package contents

- Earthing wire set
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	14.00	22.00	62.00	92.00	125,488.00
Packaging Unit Inside	1	14.00	22.00	62.00	92.00	125,488.00
Packaging Unit Single	1	14.00	22.00	62.00	92.00	125,488.00
Net single without Packaging	1	12.00	20.00	60.00	90.00	0.00

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com