DIGITUS® □□□□□□□□□ □□□□ Slim

DN-19 WM-3H3V-SL

EAN 4016032383116

Wall mounting cabinet, slim, 900x600x200 mm 3U horizontal and 3U vertical, grey (RAL 7035)

Настенный шкаф серии Slim 483 мм (19 дюймов) обеспечивает возможность горизонтальной или вертикальной установки 3U с двумя независ

Компактный дизайн шкафа с возможностью поворота внутренних монтажных зон

- Прочная листовая сталь толщиной 1,0 – 1,5 мм
- Две монтажные зоны размером по 3U
- с возможностью поворота на 100°
- На всех стенках выполнены вводы для кабелей с пластиковой крышкой
- Панель основания подготовлена к установке вентилятора
- Фронтальная дверца с запиранием выполнена с вентиляционными щелевыми отверстиями
- точность кабельной разводки обеспечивается фиксацией кабеля в нескольких точках

Attributes

- Cabinet type: Wall mounting cabinet, home automation
- Color: light grey, RAL 7035
- Depth: 200 mm
- Front door: Steel door, closed, single opening
- [illegible]y: 100 kg
- Side panels: Both sides
- Units: 3
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes
- [illegible]r
- Earthing wire set
- 2 x Keys

(145 x 70 мм)

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	14.00	22.00	62.00	92.00	125,488.00
Packaging Unit Inside	1	14.00	22.00	62.00	92.00	125,488.00
Packaging Unit Single	1	14.00	22.00	62.00	92.00	125,488.00
Net single without Packaging	1	12.00	20.00	60.00	90.00	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:





Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com