

## DIGITUS® Slim

DN-19 WM-V6U-SL  
EAN 4016032383260



### Wall mounting cabinet, slim 800x640x309 mm, 6U vertical, color grey (RAL 7035)

- Cabinet type: Wall mounting cabinet, home automation
  - Color: light grey, RAL 7035
  - Depth: 309 mm
  - Width: 640 mm
  - Front door: Steel door, closed, single opening
  - Side panels: Both sides
  - Units: 6
  - IP protection class: IP20
  - Mounted: yes
- Package contents**
- Earthing wire set
  - 2 x Keys

### Attributes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	21.00	32.00	66.00	82.00	173,184.00
Packaging Unit Inside	1	21.00	32.00	66.00	82.00	173,184.00
Packaging Unit Single	1	21.00	32.00	66.00	82.00	173,184.00
Net single without Packaging	1	19.00	30.90	64.00	80.00	0.00

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)