

DIGITUS USB-C 3.2 Gen 1 to HDMI Graphic Adapter

DA-70836 EAN 4016032385950





USB-C 3.2 Gen 1 to HDMI Graphic Adapter 1x HDMI, 4K/60Hz, Aluminium Housing, Silver/White

The USB-C 3.2 Gen 1 to HDMI Graphic Adapter is the ideal solution for connecting your notebook to a UHD TV, monitor or projector with an HDMI connection. Experience razor-sharp 4K videos and crystal-clear sound thanks to audio support for various formats. Whether for business presentations, video conferences or editing graphics, this portable adapter ensures razor-sharp images and precise color display on larger screens. Thanks to the plug-and-play function, no additional software is required and the compact, lightweight design with aluminum housing makes the adapter ideal for mobile use. The adapter is backwards compatible with older HDTVs and projectors, allowing seamless connection with existing devices.

The USB-C 3.2 Gen 1 to HDMI Graphic Adapter offers a reliable solution for razor-sharp 4K video transmission and clear audio quality, ideal for professional presentations or high-quality media playback

- Connections:
- 1x USB-C 3.2 Gen 1 Host connection

- 1x HDMI Max. Resolution: 4096 x 2160p at 60Hz
- Dimensions: 4.5 x 2.4 x 1 cm
- Weight: 20 g
- Product color: Silver
- Cable color: White Cable length: 15 cm
- Housing: Aluminum
- Power consumption: Max. 900 mA
- Chipset information: GSV2201D
- Operating system compatibility: Windows 7 or higher, macOS 10.8 or higher, iOS (iPhone 15 or higher), iPadOS, ChromeOS, Android, Linux
- Supports dual display (expand screen / mirror screen)

Attributes

USB-C Products: yes

Package contents

- 1x USB-C 3.2 Gen 1 to HDMI Graphic Adapter
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	5.00	35.00	35.00	46.00	56,350.00
Packaging Unit Inside	1	0.05	14.00	11.50	2.50	402.50
Packaging Unit Single	1	0.05	2.00	8.50	14.00	238.00
Net single without Packaging	1	0.02	1.00	2.40	4.50	0.00



More images:





















Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- · Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com