


# DIGITUS® CAT 6, I

DK-1617-050/Y  
EAN 4016032387954



**CAT 6 U-UTP patch cord, Cu, LSZH AWG 26/7, length 5 m, color yellow**

DIGITUS® CAT 6. 250 MHz, 100 Ohm, 4 x 2 AWG 26/7, twisted pair, LSZH, 5 m, yellow, RJ45 (8P8C) plug, RJ45 (8P8C) plug, Category: CAT 6

- 2 RJ45 (8P8C)
- 250 MHz, 100 Ohm, 4 x 2 AWG 26/7, twisted pair, LSZH, 5 m, yellow, RJ45 (8P8C) plug, RJ45 (8P8C) plug
- 250 MHz, 100 Ohm, 4 x 2 AWG 26/7, twisted pair, LSZH, 5 m, yellow, RJ45 (8P8C) plug, RJ45 (8P8C) plug
- Material: Copper (Cu)





**Attributes**

- Assortment: Twisted Pair Patch Cables

- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DigiTUS Polybag
- Category: CAT 6
- Shielding: U-UTP, unshielded
- Length: 5 m
- Color: yellow
- Jacket: LSOH
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair
- Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	70	10.00	46.00	32.00	27.00	39,744.00
Packaging Unit Inside	10	1.43	20.00	30.00	36.00	21,600.00
Packaging Unit Single	1	0.14	2.00	17.00	25.00	850.00
Net single without Packaging	1	0.12	500.00	1.20	1.30	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)