

DIGITUS® Módulo SFP de cobre de 1,25 Gbps, RJ45

DN-81005

EAN 4016032389484



Módulo SFP de cobre de 1,25 Gbps, RJ45 10/100/1000Base-T, até 100 metros

Os módulos transceptores DIGITUS® Mini GBIC (SFP) oferecem a mais elevada qualidade e fiabilidade. O módulo oferece a oportunidade perfeita para expandir o seu computador de rede Gigabit com uma porta de ligação ascendente SFP gratuita através de uma ligação RJ45 adicional. Graças à sua capacidade de "hot-plug", pode instalar o módulo sem interromper o tráfego de rede ou reiniciar o dispositivo. A conformidade com a norma MSA (Multi Source Agreement) também garante a compatibilidade com os fabricantes de computadores de rede mais comuns.

A extensão plug and play para o seu switch de rede

- Módulo Mini GBIC SFP (Small Form Fator Pluggable)
- Compatível com os seguintes fabricantes: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Débito máximo de dados bidirecional até 1,25 Gbps
- Em conformidade com a norma IEEE 802.3z Gigabit

- Alta qualidade e máxima fiabilidade
- Fácil instalação plug and play
- Compatível com MSA (Multi Source Agreement)
- Ligação a quente - possibilidade de instalação durante o funcionamento
- Auto MDI/MDI-X
- Ligação: 1x RJ45, CAT 5
- Distância: até 100 m
- Temperatura de funcionamento: 0 °C ~ 70 °C

Attributes

- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- Módulo SFP

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 120 | 7.00 | 25.40 | 39.40 | 55.00 | 55,041.80 |
| Packaging Unit Inside | 30 | 1.75 | 7.00 | 20.00 | 30.00 | 4,200.00 |
| Packaging Unit Single | 1 | 0.06 | 3.20 | 9.30 | 12.00 | 357.12 |
| Net single without Packaging | 1 | 0.02 | 1.50 | 1.50 | 7.00 | 0.00 |

More images:



| Product Number | SKU Code | Speed | Distance | Connector | Wavelength | Operating Temperature | Industrial Version |
|----------------|--------------|----------|----------|---------------------|---------------|-----------------------|--------------------|
| DM-4100 | 401000000000 | 1.0 Gbps | 200m | LC Multimode Duplex | 1310nm | 0 to 70 °C | |
| DM-4101 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4104 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4105 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm | 0 to 70 °C | |
| DM-4106 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm | 0 to 70 °C | |
| DM-4107 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4108 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4109 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm | 0 to 70 °C | |
| DM-4110 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4111 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm | 0 to 70 °C | |
| DM-4112 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm | 0 to 70 °C | |
| DM-4113 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4114 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4115 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm | 0 to 70 °C | |
| DM-4116 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm | 0 to 70 °C | |
| DM-4117 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4118 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4119 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |
| DM-4120 | 401000000000 | 1.0 Gbps | 200m | LC Duplex Duplex | 1310nm/1550nm | 0 to 70 °C | |

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com