DIGITUS® SFP+ 10 Gbps Bi-directional Module, Singlemode, TX1270/RX1330, 10km

DN-81204

EAN 4016032424260



10G SFP+ Module, Singlemode, BiDi, DDM LC Simplex Connector, Tx1270/Rx1330, up to 10km

□□□□□□□ □□□□□□□□□□□□□ DIGITUS® Mini GBIC (SFP) □□□□□□□□□□□□□□ □□□□□□□□□□□ □□□□□□□□□□ □ □□□□□□□□□□□□ □□□□□ □□ □□□□□□□□□□□ □□□□□□ □□□□□□□□□□□□□□□□, □ Source Agreement) □□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□ □ □ □□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□.

□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□ Plug and Play

- □□□□□□□□□□ □ □□□□□□□□□□□□□□□ □□□□□□□□□□□ □□□□□□□□□□□□□□□□□□: Allied Telesis, Alinet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik , ENTERASYS, RIVERSTONE , Unifi, Ubiquiti, ZyXEL, ZTE
- □□□□ □□□□□□□□□□□□□: 1 □□□□□□□□□□ LC
- □□□□□□□□□□□□□□□□□□ □□□□□□□ WDM — □□□□□□□□□□ □□□□□□□ □□□□□ □□□□□□□□
- □□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□
- □□□□□□□□ □□□□□□□□□□ □ □□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□
- □□□□□□ 1 □□□□□□□□□□ □□□□□□□□ □□ EN 60825-1
- □□□□□□□□ □□□□□□□□□□□ Plug and Play
- □□□□□□□□□□□ □□ □□□□□□□□□□□□□ MSA (□□□□□□□□□ □□□□□□□□□□□□□)
- □ □□□□□□□□□□□□□□□ □□□□□□□□□□□□□□ □□□□□□□□
- □□□□□□□□□□□□□□□□□ 3,3 □
- □□□□□□□□□□ □□□□ □□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□ □□□□□□□□ 09/125µ□
- □□□□□□□□ □□□□□□□□□□□□□□: 0-70 °C

Attributes

- Mode: Singlemode
- Connector: LC
- Distance (km): 10
- Wavelength: 1270/1330 nm
- DDM Support: yes
- Broadcasting Mode: Biidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: 10 Gigabit

Package contents

- 10G SFP+ Module

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	7.00	55.00	39.50	25.50	55,398.80
Packaging Unit Inside	1	0.06	11.70	9.30	3.20	348.19
Packaging Unit Single	1	0.06	11.70	9.30	3.20	348.19
Net single without Packaging	1	0.03	6.00	0.80	1.00	0.00

More images:







Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com