

DIGITUS® MPO/MTP patch panel for 3 cassettes, 1U, unequipped

DN-96613-2

EAN 4016032424390



MPO/MTP panel for 3 cassettes Empty panel, not incl. cassette, pigtails, couplers

The patch panel is the ultimate solution for networks that require a high-density, organized and future-proof fiber optic connection. It is a compact, high-performance solution designed for efficient cable management and seamless connectivity in modern data centers, telecom and enterprise networks. It offers a versatile, modular platform to accommodate up to three MPO/MTP cassettes in a single panel. This patch panel has a plug-and-play functionality that allows for quick installation and simplified network upgrades. Pre-terminated MPO/MTP trunk cables can be connected to the rear panel, while the front panel is equipped with standard connectors such as LC or SC to ensure a streamlined, organized and reliable network setup.

The MPO/MTP patch panel provides high-density connectivity and seamless scalability for network upgrades. It ensures reliable performance for high-speed networks in data centers and telecommunication systems.

- 19" housing
- Unassembled
- For 3 x MTP/MPO cassettes
- Extendable
- Color black

Attributes

- Assembly: Empty housing
- Color: black, RAL 9005
- Type: fixed

Package contents

- 1 x MPO/MTP patch panel for 3 cassettes, 1U, not mounted

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	4	10.30	30.00	53.00	23.00	36,570.00
Packaging Unit Inside	1	2.58	0.00	0.00	0.00	0.00
Packaging Unit Single	1	2.58	28.50	51.50	5.20	7,632.30
Net single without Packaging	1	2.10	20.60	48.20	4.40	0.00

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com