


Digitus® Jednostrani OS2 pigtaili u jednoboju LC/APC izvedbi

DK-29332-02/APC

EAN 4016032428848



DK-29332-02/APC pigtail kabel SM LC(APC) loose buffer, color code DIN IEC 304, 2 m

DIGITUS® optički vlaknasti pigtail kabeli dostupni su u LC simplex, SC simplex i ST simplex verzijama te vam nude izvrsne performanse i kvalitetu veze za vašu mrežu s klasama OS2, OM2, OM3 i OM4. Konektor je u skladu sa standardom IEC 61754-4 2002 i opremljen je keramičkom ferulom od cirkonije. Setovi obojenih vlakana označeni su prema standardu IEC 304 (bijela, ljubičasta, tirkizna, crna, crvena, ružičasta, narančasta, siva, zelena, žuta, smeđa, plava).

Standardima usmjereni prema budućnosti i vrhunska kvaliteta za vašu mrežu.

- Simplex OS2 09/125 μ 2 m
- Konektori u skladu sa standardom IEC 61754-4 2002
- Radna temperatura: -25 °C do +80 °C
- Raspon temperatura za transport i skladištenje: -20 °C do +65 °C
- Gubitak umetanja MM PC: max. 0,4 dB

- Gubitak povrata MM PC: > 25 dB
- Keramička ferula od cirkonije
- Dimenzije sekundarnog premaza: $\varnothing 0,9 \pm 0,1$ mm
- Osnovni premaz: akrilati; $\varnothing 250 \pm 15$ μ m
- Setovi obojenih vlakana u skladu s IEC 304 u sljedećim bojama: bijela, ljubičasta, tirkizna, crna, crvena, ružičasta, narančasta, siva, zelena, žuta, smeđa, plava
- 12 komada po pakiranju
- Slobodni međuspremnik


Attributes

- Klasa vlakna: OS2
- Konektor 1: LC (APC)
- Mod: Jednomodni
- Promjer vlakna: 9/125 μ
- Stopica: jednoboju
- Duljina: 2 m

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	160	10.40	45.00	45.00	40.00	81,000.00
Packaging Unit Inside	1	0.07	17.00	19.00	0.10	32.30
Packaging Unit Single	1	0.07	17.00	19.00	0.10	32.30
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com