

# DIGITUS® 4K HDMI, HDBaseT™ 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)

DS-55500

EAN 4016032429449



## 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)

Digitus 4K, HDBaseT™ 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7) is a high-quality video extender set that allows you to extend your 4K HDMI signal up to 70 meters over standard Cat 5E, 6, or 7 network cables. The set includes two 4K HDMI Extender Set units, one for the transmitter and one for the receiver. The transmitter unit has an HDMI input and a network port, while the receiver unit has an HDMI output and a network port. The set also includes a 3D HDTV, a CEC receiver, and a CEC transmitter. The set is compatible with 4K (30 Hz), 1080p, 1080i, 720p, 576p, 576i, 480p, and 480i. The set is also compatible with HDBaseT™, HDCP 2.2, DTS Digital, and Dolby Digital. The set is also compatible with DTS Digital, Dolby Digital, DTS Digital, and Dolby Digital. The set is also compatible with DTS Digital, Dolby Digital, DTS Digital, and Dolby Digital.

- 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)
- 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)
- 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)

- Attributes**
- HDMI Standard: Ultra HD 4K
  - Resolution max: 4096 x 2160 Pixel, 30Hz
  - Category: CAT 5e
  - Distance: 40 m
  - KVM: no
  - PoE (Power over Ethernet): no

- Package contents**
- 1 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)
  - 1 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)
  - 2 4K HDMI Extender Set, HDBaseT™, UHD 4K\*2K@30Hz 70m over network cable (Cat 5E, 6, 7)
  - 1 3D HDTV
  - 1 CEC receiver
  - 1 CEC transmitter
  - 1 DTS Digital, Dolby Digital
  - 1 DTS Digital, Dolby Digital
  - 1 DTS Digital, Dolby Digital

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	17.92	42.50	31.00	41.50	54,676.20
Packaging Unit Inside	1	0.90	19.90	14.90	8.00	2,372.08
Packaging Unit Single	1	0.90	19.90	14.90	8.00	2,372.08
Net single without Packaging	1	0.03	9.90	6.70	2.30	0.00

**More images:**



**Safety notes**

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)