

DIGITUS® Mini HDMI

DS-55203

EAN 4016032435006



Mini HDMI Extender Set, Full HD, 1080p 50m, Cat6/6A/7, powered via Micro USB cable, bk

Digitus Mini HDMI Extender Set, Full HD, 1080p 50m, Cat6/6A/7, powered via Micro USB cable, bk. This set includes a Mini HDMI Receiver and a Mini HDMI Transmitter, both in black. The receiver has a Mini HDMI port on the front and a Micro USB port on the back. The transmitter has a Mini HDMI port on the front and an RJ45 Ethernet port on the back. Both devices are powered via a Micro USB cable.

Attributes

- Operating temperature: -10 ~ 70° C
- Relative humidity (non-condensing): 0 ~ 90%
- Dimensions (L x W x H): 71 x 26 x 11 mm
- Material: ABS
- Color: Black
- Cable length: 10 m
- Category: CAT 6
- Distance: 50 m
- PoE (Power over Ethernet): yes
- HDCP 1.2
- Standards: CAT 6, CAT 6A, CAT 7
- Standard: IEEE-568B
- HDMI: 10,2 pins (19 pins)
- Material: ABS
- Operating temperature: 0 ~ 50° C

- Operating temperature: -10 ~ 70° C
- Relative humidity (non-condensing): 0 ~ 90%

Attributes

- Operating temperature: -10 ~ 70° C
- Relative humidity (non-condensing): 0 ~ 90%
- Dimensions (L x W x H): 71 x 26 x 11 mm
- Material: ABS
- Color: Black
- Cable length: 10 m
- Category: CAT 6
- Distance: 50 m
- PoE (Power over Ethernet): yes
- HDCP 1.2
- Standards: CAT 6, CAT 6A, CAT 7
- Standard: IEEE-568B
- HDMI: 10,2 pins (19 pins)
- Material: ABS
- Operating temperature: 0 ~ 50° C

Package contents

- 1 Mini HDMI Receiver
- 1 Mini HDMI Transmitter
- 2 Micro USB (1,0 m)
- Cable length: 10 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	60	9.60	43.00	33.00	38.00	53,922.00
Packaging Unit Inside	1	0.16	11.40	7.80	5.80	515.74
Packaging Unit Single	1	0.16	11.40	7.80	5.80	515.74
Net single without Packaging	1	0.02	7.20	2.60	1.20	0.00

More images:



Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com