

# DIGITUS® USB-C connection cable, USB-A - USB-C

AK-300148-030-S  
EAN 4016032437482



**USB Type-C connection cable, type USB-A to USB-C M/M, 3.0m, 5V3A, 15W, 480MB, 2.0 Version, bl**

For connecting external USB end devices (with C socket, e.g. tablet, notebook or smartphone) to the USB host (e.g. PC or notebook). Transfer rate up to 480 Mbps (high-speed).

**For super-fast synchronization and charging**

- High USB data transfer rate up to 480 Mbps
- Supports up to 5V3A, 15W power supply
- Supports the USB PD (Power Delivery) specification.
- Type C plug can be used on both sides

**Attributes**

- Ambalaža: Polybag
- Asortiman: USB kabeli
- AWG: 30/22
- Kabel u boji: crni
- Kapice: ukalupljeno
- Konektor 1: USB A, utikač
- Konektor 2: USB C, utikač
- Konektor u boji: crni
- Materijal žice: CU
- Površina konektora: poniklano
- Duljina: 3 m
- oklop: dvostruki oklop
- USB-C proizvodi: Da

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	100	11.67	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	1.17	24.00	22.00	9.00	4,752.00
Packaging Unit Single	1	0.12	16.00	1.50	22.00	528.00
Net single without Packaging	1	0.10	13.00	13.00	4.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)