

# DIGITUS Соединительный кабель с разъёмом USB Type-C, Type-C на B

AK-300149-018-S EAN 4016032437529



# USB Type-C connection cable, type C to B M/M, 1.8m, 3A, 5GB, 3.0 Version, bl $\,$

Для подключения внешних устройств USB 3.0 (с разъёмом типа В, например, внешних жестких дисков, сканера или принтера) к USB-хосту (например, ПК, ноутбуку или USB-разветвителю). Скорость передачи данных до 5 Гбит/с (Super-Speed).

### Штекер Туре-С, используется двусторонне

- Высокоскоростная передача данных до 5 Гбит/с в 10 раз быстрее, чем USB 2.0
- Поддерживает электропитание до 3 А
- Поддерживает спецификацию USB PD (подача мощности).
- Штекер Туре-С, используется двусторонне

#### Coni

Color cable: black
 Color cable: black

AWG: 24/28

- Color connector: black
- Connector 1: USB C, plugConnector 2: USB B, plug

Assortment: USB Cables

- Connector surface: nickel-plated
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 1.8 m
- · Shielding: Double shielding
- USB-C Products: yes

# Attributes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	10.20	50.00	32.00	21.00	33,600.00
Packaging Unit Inside	10	0.85	35.00	28.00	7.00	6,860.00
Packaging Unit Single	1	0.09	13.00	24.00	4.50	1,404.00
Net single without Packaging	1	0.08	13.00	12.00	4.50	0.00

#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- · Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
  operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.



## EU responsible person

EU based economic operator ensuring the product complies with the required regulations. ASSMANN Electronic GmbH Auf dem Schüffel 3  $\,$ 

Lüdenscheid, Germany https://www.assmann.com info@assmann.com