

DIGITUS® DisplayPort, DP – HDMI Adapter Cable

AK-340303-010-S
EAN 4016032438588



DisplayPort adapter cable, DP – HDMI type A M/M, 1.0m, w/lock, DP 1.2_HDMI 2.0,4K/60Hz, CE,bi

Digitus DisplayPort Adapter Cable DP – HDMI type A M/M, 1.0m, w/lock, DP 1.2_HDMI 2.0,4K/60Hz, CE,bi. This cable is designed for connecting a DisplayPort source to an HDMI destination. It features a DisplayPort connector on one end and an HDMI type A connector on the other. The cable is 1.0m long and includes a lock mechanism for secure connection. It supports video resolutions up to 4K/60Hz and is compatible with HDMI 2.0. The cable is CE certified and includes a Plug-and-Play feature for easy setup.

- Supports HDMI 2.0
- Supports 4K/2K @ 60 Hz
- Supports 3D @ 1080p
- Supports HDCP & DPCP

Attributes

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black

- Color connector: black
- Connector 1: DP, plug
- Connector 2: HDMI type A, plug
- Connector surface: nickel-plated
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 1m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	140	9.38	50.00	32.00	21.00	33,600.00
Packaging Unit Inside	10	0.67	40.00	34.00	9.60	13,056.00
Packaging Unit Single	1	0.07	16.00	24.00	4.80	1,843.20
Net single without Packaging	1	0.05	16.00	24.00	4.80	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com