

# DIGITUS® DisplayPort, DP – HDMI Adapter Cable

AK-340303-020-S  
EAN 4016032438595



**DisplayPort adapter cable, DP – HDMI type A M/M, 2.0m, w/lock, DP 1.2\_HDMI 2.0,4K/60Hz, CE, bi**

Digitus DP to HDMI Adapter Cable is a high quality cable that allows you to connect your DisplayPort source to your HDMI destination. It is a Plug-and-Play cable that does not require any drivers or software. It is a 2.0m long cable with a locking mechanism on the HDMI connector. It is a high quality cable that is made of copper wire and has a triple shielding. It is a high quality cable that is made of copper wire and has a triple shielding.

- Supports HDMI 2.0
- Supports 4K/2K @ 60 Hz
- Supports 3D @ 1080p
- Supports HDCP & DPCP

**Attributes**

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black

- Color connector: black
- Connector 1: DP, plug
- Connector 2: HDMI type A, plug
- Connector surface: nickel-plated
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

**Logistics**

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	50	5.60	25.00	32.00	44.00	35,200.00
Packaging Unit Inside	10	1.12	7.00	16.00	30.00	3,360.00
Packaging Unit Single	1	0.11	16.00	24.00	4.80	1,843.20
Net single without Packaging	1	0.09	2.00	12.00	11.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)