

# DIGITUS® Cabo adaptador DisplayPort, DP - HDMI tipo A

AK-340303-030-S

EAN 4016032438601



**Cabo adaptador Displayport, tipo DP - HDMI tipo A St/St,3.0m, c/ bloqueio,4K@60Hz, DP 1.2,HDMI 2.0,bw**

Este cabo áudio/vídeo digital HD de elevado desempenho é utilizado para ligar PCs ou computadores portáteis a monitores com uma interface HDMI.

**Ignorar adaptadores com um adaptador de cabo plug-and-play que não requer uma fonte de alimentação externa.**

- Suporta funcionalidades HDMI 2.0
- Suporta até 4K/2K com 60Hz
- Suporta 3D com uma resolução de 1080p
- Suporta HDCP e DPCP
- Modos de transmissão suportados: RBR, HBR, HBR2
- Largura de banda máxima: 21,6 Gbps
- Versão HBR/modo de transferência: HBR2 (5,40 Gbit/s por via)

**Attributes**

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: HDMI type A, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 3 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	40	5.60	25.00	35.00	55.00	48,125.00
Packaging Unit Inside	10	1.40	10.00	24.00	38.00	9,120.00
Packaging Unit Single	1	0.14	4.80	24.00	16.00	1,843.20
Net single without Packaging	1	0.13	2.00	17.00	17.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)