

# DIGITUS® 10 Gigabit

DN-82211

EAN 4016032441175



## 10 Gigabit Ethernet Media Converter, SFP supports 1G, 2.5G, 5G and 10G, open slot

- DIGITUS® 10 Gigabit Ethernet Media Converter, SFP supports 1G, 2.5G, 5G and 10G, open slot
- 1 RJ45 / 1 SFP
- 1000Base-T / 1000Base-X, 2.5G Base-T / 2.5G Base-X, 5G Base-T / 5G Base-X, 10G Base-T / 10G Base-X
- 80 mm
- 0 to 55°C

- 10 Gigabit Ethernet Media Converter, SFP supports 1G, 2.5G, 5G and 10G, open slot

### Attributes

- Connector 1: RJ45
- Connector 2: SFP
- Mode: Depending on module
- Distance (km): Depending on module
- Industrial usage: no
- Broadcasting Mode: Unidirectional
- PoE injector: no
- Ethernet speed: 10 Gigabit


### Package contents

- 10 Gigabit Ethernet Media Converter
- 10 Gigabit Ethernet Media Converter

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	8.00	40.00	26.00	34.00	35,360.00
Packaging Unit Inside	1	0.40	24.00	13.00	6.00	1,872.00
Packaging Unit Single	1	0.40	24.00	13.00	6.00	1,872.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

**More images:**



**Safety notes**

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)