

DIGITUS® Repartidor Industrial Gigabit PoE++, 802.3bt

DN-651111

EAN 4016032441182



Repartidor Industrial Gigabit PoE++, 802.3bt tensão selecionável: 12VDC, 16VDC, 24VDC, 48VDC

O Repartidor Industrial Gigabit PoE DIGITUS® foi concebido para ambientes agressivos, onde estão expostos à humidade, flutuações de temperatura e vibrações. Com uma gama de temperaturas de -40°C a 75°C, o Splitter Industrial Gigabit PoE pode ser utilizado nas condições mais adversas. A disponibilidade constante é garantida em áreas altamente sensíveis, como transporte, produção, tráfego e vigilância de segurança. Graças ao sistema simples plug-and-play, o Splitter Industrial Gigabit PoE pode ser rapidamente integrado no respetivo ambiente. O DIGITUS® DN-651111 é um repartidor Industrial Gigabit PoE Plug & Play não gerido, numa robusta caixa de alumínio com proteção IP30. Graças à conectividade Gigabit e à tensão selecionável que pode ser fornecida para dispositivos não compatíveis com PoE, o Divisor Industrial Gigabit PoE é uma solução flexível e económica para ambientes industriais. A tensão de alimentação pode ser selecionada na gama de 12VDC, 16VDC, 24VDC ou 48VDC. A norma IEEE802.3bt permite uma alimentação PoE de até 95 watts. São fornecidas duas saídas de alimentação paralelas para dispositivos finais.

- Repartidor Gigabit com fonte de alimentação PoE até 95 watts
- Tensão de saída ajustável de forma flexível: 12VDC, 16VDC, 24VDC, 48VDC

- Saída de dados Gigabit para ligação à rede
- Retrocompatível com a norma IEEE802.3af/at
- Tecnologia store-and-forward para uma transferência de dados otimizada
- Função Auto MDI/MDI-X
- LEDs de diagnóstico para monitorização do estado e da atividade
- Temperatura de funcionamento: -40°C a +75°C
- Dispositivo Consumo de energia (máx.): 1W

Attributes

- PoE standard: IEEE802.3bt (PoE++)
- Ethernet speed: Gigabit
- Power output: 55 W
- Industrial usage: yes
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: no

Package contents

- Repartidor Industrial Gigabit PoE++, 802.3bt
- Guia de início rápido

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	16	7.00	56.00	35.00	24.00	47,040.00
Packaging Unit Inside	1	0.44	21.50	6.50	16.50	2,305.88
Packaging Unit Single	1	0.44	21.50	6.50	16.50	2,305.88
Net single without Packaging	1	0.15	10.40	3.20	8.20	0.00

More images:



Safety notes

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
 - The mains cable, power supply unit or plug for the power supply is damaged or worn;
 - Liquid has penetrated the appliance;
 - The device has been exposed to rain or water;
 - The device has been dropped or the housing has been damaged;
 - The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com