

DIGITUS® CAT 6 S/FTP patch cable, 10 pieces

DK-1644-0025-BL-10

EAN 4016032441328



CAT 6 S-FTP patch cord, Cu, LSZH AWG 27/7, length 0.25 m, 10 pieces, color black

Digitus® CAT 6 S/FTP patch cord, Cu, LSZH AWG 27/7, length 0.25 m, 10 pieces, color black. This is a 250m long, black, Digitus® CAT 6 S/FTP patch cord. It is made of copper (Cu) and has a length of 0.25 m. The cable is made of LSZH (Low Smoke Zero Halogen) material and has a twisted pair structure. The cable is shielded with S-FTP (Shielded Foiled Twisted Pair) technology, which consists of pairs in metal foil and braid shielding. The cable is made of 4 x 2 AWG 27/7, twisted pair. The cable is made of LSZH material and has a length of 0.25 m. The cable is made of LSZH material and has a length of 0.25 m. The cable is made of LSZH material and has a length of 0.25 m.






- 2 RJ45 (8P8C)
- LSZH (Low Smoke Zero Halogen)
- Shielded (S-FTP)
- Conductor: Cu (Cu)

Attributes

- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: Digitus Polybag
- Category: CAT 6
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Length: 0.25 m
- Color: black
- Jacket: LSOH
- Slim Version: no
- Structure: 4 x 2 AWG 27/7, twisted pair
- Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	25	4.90	36.00	36.00	24.00	31,104.00
Packaging Unit Inside	1	0.20	5.20	22.00	28.00	3,203.20
Packaging Unit Single	1	0.20	1.60	11.50	21.00	386.40
Net single without Packaging	1	0.02	25.00	1.20	1.30	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com