


DIGITUS® CAT 7 S/FTP data cable - installation cable, 500 m, duplex, Cca

DK-1744-VH-D-5

EAN 4016032441762



CAT 7 S-FTP installation cable, 1200 MHz Cca (EN 50575), AWG 23/1, 500 m drum,

The Digitus Cat 7 installation cable is designed for use in structured data centers and building cabling in accordance with ISO/IEC 11801, DIN EN 50288-4-1, DIN EN 50173, IEC 61156-7, EN 50288-9-1. The cable is ideal for the transmission of analog and digital data and supports PoE, PoE+, 4PPoE (IEEE 802.3af;3at;3bt). The shield structure consists of individually shielded pairs with a tinned copper braid, which ensures excellent shielding and electrical values.

Future-oriented standards and high-end quality for your network.

- Physical properties:
- Conductor: Bare copper wire, AWG 23/1
- System(s) of assessment and verification of constancy of performance: System 3
- Insulation: SFS-PE (foamed polyethylene jacket)
- Total number of insulated conductors: 8, twisted into 4 pairs
- Color code: Blue-white, orange-white, green-white, brown-white
- Shielding of the individual pairs: aluminum-laminated polyester film, covers 100%
- Overall shielding: copper braiding
- Outer sheath: Cca acc. to EN 50575; LSZH
- Color: Orange (RAL 2008)
- Mechanical properties:
- Strain relief: 135N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Transport and storage temperature range: -20 °C to +60 °C

- Operating temperature range: -20 °C to +50 °C
- Installation temperature range: 0 °C to +50 °C
- Electrical properties:
- Impedance: 100±15 Ohm @ 4 - 1000 MHz; 100±25 OHM @ 100-600 MHz
- Capacitance: 45pF/m nom. at 1KHz
- Capacitance: 40 pF/m nominal @ 1 KHz
- Insulation resistance: 5 GOhm x km min.
- DC resistance: 95 Ohm/km max. (2% max. unbalanced resistance)
- Loop resistance: 190 Ohm/km max. (2% max. unbalanced resistance)
- Operating voltage: 72 Vdc max.
- Coupling attenuation: CA-Type 1b
- Phase delay: 450 nS/100 m max.
- Time delay: 10 nS/100 m max.
- Separation class: "d" according to EN 50174-2
- NVP: 79%
- Flame spread: EN EN 60332-1-2 (LSOH-PVC)
- Halogen-free, corrosivity: EN 60754-1/2 (LSOH)
- Smoke density EN 61034-2


Attributes

- Assortment: Twisted Pair Installation Cables
- Category: CAT 7
- Shielding: S-FTP, pairs in metal foil and braid shielding
- CPR: Cca
- Length: 500 m
- Color: orange
- Jacket: LSOH
- Structure: 4 x 2 AWG 23/1, solid twisted pair

Logistics




	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	54.70	55.00	55.00	38.00	114,950.00
Packaging Unit Inside	1	54.70	55.00	55.00	35.00	105,875.00
Packaging Unit Single	1	54.70	55.00	55.00	38.00	114,950.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Produktinformation Product Information		Physikalische Spezifikationen Physical Properties	
Produktname Product Name	DK-1743-VH-D-5 CAT 7 S/FTP Installation Cable, 500m, Duplex, Dca	Standard Standard	ISO/IEC 11801 Class E, ANSI/TIA-568 Class F
AWG	23/1	Shielding Type	Shielded
Frequency	1200 MHz	Shielding Effectiveness	> 100 dB
Bandwidth	10 Gbit Ethernet	Temperature Range	-20°C to +70°C
Category	CAT 7	Humidity	10% to 90% RH
Shielding	LSZH	Flammretardant	Yes
Material	Dca	RoHS	Compliant
Lead-free	Yes	REACH	Compliant

Leitungsparameter Transmission Properties											
Parameter	Unit	Value	Unit								
Attenuation	dB/100m	1.5	dB/100m								
Return Loss	dB	20	dB								
Shielding Effectiveness	dB	>100	dB								



Parameter	Value	Parameter	Value
Category	B2+	Shielding	LSZH
Material	Cca	Flammretardant	Yes
Shielding	Dca	RoHS	Compliant
Lead-free	Eca	REACH	Compliant
Lead-free	Yes	Lead-free	Yes



Safety notes

- Data cables must not be bent, stretched or twisted excessively. Sharp bends can damage the cable sheath and lead to failures or short circuits.
- Installation only by trained specialists.
- Installation only in dry rooms.
- The data cable must not be in direct contact with other electrical cables or high-voltage sources in order to avoid electromagnetic interference.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
 info@assmann.com