

DIGITUS® Front panel and mounting frame for multimedia with 2 x DN-93615 Keystone modules

DN-93831-2

EAN 4016032444398



Front plate 50x50 central plate, RAL9003 with 2x DN-93615-S Keystone Modules

The DIGITUS® network connection module with CAT 6A compact keystone combipack offers a comprehensive and reliable solution for high-performance structured cabling installations. The front panel is designed for seamless integration with shielded DIGITUS® Keystone modules and features integrated dust protection flaps that protect the connector from dust and external contamination, while the vertical orientation of the module at a 45° angle allows convenient cable routing and easy access to the patch cables. The included shielded CAT 6A Compact Keystone module (DN-93615-S) supports high-speed data transmission and future-proof network standards and offers tool-free installation and 360° shielding. Its compact design allows flexible use in compatible modular ports and high-density installations. By combining both components in one package, the solution ensures guaranteed compatibility while simplifying procurement and installation.

Provides a ready-to-install network connection solution that reduces installation effort while ensuring precise component compatibility and a reliable connection.

- Junction box with angled outlet to accommodate Keystone modules
- Insertion direction of the module 45° vertically inclined
- Compatible with shielded DIGITUS® CAT 6A Keystone modules e.g. DN-93615, DN-93617 & DN-93619
- Design compatible with all common switch ranges
- Can be used as a 1-port and 2-port data socket
- Suitable for installation in trunking, flush-mounted & surface-mounted
- Material empty housing: die-cast metal
- Operating temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- including 2X DN-93615 Keystone modules
- Network combination connection: DN-93831-2 - DN-93831 + 2 x DN-93615-S

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	360	5.42	31.00	53.00	22.00	36,146.00
Packaging Unit Inside	10	0.15	16.00	6.50	7.50	780.00
Packaging Unit Single	1	0.02	13.00	8.00	1.50	156.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com