

DIGITUS Conversor de Média SFP Modo Múltiplo/Modo Simples

DN-82133
EAN 4016032445753



Gigabit Multimode to Singlemode Media Converter SFP to SFP, 155Mbps, 1.25Gbps, 850nm to 1550nm

Os conversores de média da DIGITUS® consistem na solução ideal para a migração de sinais de fibra de vidro. A partir de agora, é possível aceder à tecnologia de fibra e transferir os sinais de rede ao longo de vários quilómetros sem ter de substituir toda a infra-estrutura de rede. A nossa grande variedade de produtos corresponde às suas necessidades individuais. O funcionamento intuitivo garante uma instalação fácil e rápida. Os anos de experiência e a grande variedade de produtos permitem que a DIGITUS® se torne num parceiro fiável para a sua engenharia de rede.

A solução de conversão ideal para transmissão de dados óticos

- Converte entre fibra de vidro de modo múltiplo/modo simples
- 2 x Ligação, 100/1000Base-X SFP
- Comprimento de onda: 850nm, 1310nm (Modo Múltiplo), 1310nm, 1550nm (Modo Simples)
- LED de diagnóstico sobre o estado e monitorização de atividade
- Adequado para cabos de fibra de vidro (modo múltiplo) 50/125µm, 62,5/125µm e 100/140µm
- Adequado para cabos de fibra de vidro (modo simples) 8,3/125µm, 8,7/125µm, 9/125µm e 10/125µm

- Temperatura de funcionamento: -10 até 55°C
- Conversor Standalone com fonte de alimentação externa
- Tensão de entrada: 5V DC
- Corrente de entrada máx.: 1 A
- Consumo de energia: 3,5W
- Dimensões (C x L x A): 95mm x 70mm x 26mm

Attributes

- Connector 1: SFP
- Connector 2: SFP
- Mode: Multimode -> Singlemode
- Distance (km): Depending on module
- Industrial usage: no
- Broadcasting Mode: Depending on module
- PoE injector: no
- Ethernet speed: Gigabit

Package contents

- Conversor de Média SFP Modo Múltiplo/Modo Simples
- Peso: 20 g
- Fonte de alimentação

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	7.00	55.00	39.40	25.40	55,041.80
Packaging Unit Inside	1	0.35	25.00	13.00	5.50	1,787.50
Packaging Unit Single	1	0.35	25.00	13.00	5.50	1,787.50
Net single without Packaging	1	0.30	7.00	9.50	2.60	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.

- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3

Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com