DIGITUS Многомодовый/одномодовый гигабитный медиапреобразователь SFP

DN-82133
EAN 4016032445753

Gigabit Multimode to Singlemode Media Converter SFP to SFP, 155Mbps, 1.25Gbps, 850nm to 1550nm

Медиапреобразователи DIGITUS® являются идеальным решением для перехода к оптоволоконным сетям. Теперь можно передавать сигналы по оптоволоконным сетям на несколько километров без обновления всей сетевой инфраструктуры. Широкая линейка устройств позволяет удовлетворять любые индивидуальные потребности. Интуитивный интерфейс обеспечивает быструю и легкую установку. Многолетний опыт работы нашей компании и широкий ассортимент продукции позволяют DIGITUS® стать вашим надежным партнером.

Преобразователь идеально подходит для передачи данных по оптоволокну

- Преобразует одномодовое оптоволокно в многомодовое
- 2 порта 100/1000Base-X SFP, подключение
- Длина волны: 850 и 1310 нм (многомодовый), 1310 и 1550 нм (одномодовый)
- Диагностические светодиодные индикаторы для контроля статуса и работы
- Подходит для оптических кабелей 50/125, 62,5/125 и 100/140 мкм (многомодовых)
- Подходит для оптических кабелей 8,3/125, 8,7/125, 9/125 и 10/125 мкм (одномодовых)
- Рабочая температура: от -10 до 55 °C
- Отдельный преобразователь с внешним блоком питания
- Входное напряжение: 5 В пост. тока
- Макс. входной ток: 1 A
- Потребление тока: 3,5 Вт
- Размеры (Д x Ш x В): 95 x 70 x 26 мм

Attributes

- Connector 1: SFP
- Connector 2: SFP
- Mode: Multimode -> Singlemode
- Distance (km): Depending on module
- Industrial usage: no
- Broadcasting Mode: Depending on module
- PoE injector: no
- Ethernet speed: Gigabit

Package contents

- Многомодовый/одномодовый гигабитный медиапреобразователь SFP
- Краткое практическое руководство
- Блок питания

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	7.00	55.00	39.40	25.40	55,041.80
Packaging Unit Inside	1	0.35	25.00	13.00	5.50	1,787.50
Packaging Unit Single	1	0.35	25.00	13.00	5.50	1,787.50
Net single without Packaging	1	0.30	7.00	9.50	2.60	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.

- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com