DIGITUS® □□□□□□ DAC SFP+ 10G 0,5 □

DN-81220

EAN 4016032445937



10G SFP+ DAC Cable 0.5m, AWG 30
Allnet,CISCO,Dell,D-Link,Edimax,Etherwan,Fortinet,

□□□□□□□ DAC SFP+ 10G □□ Digitus® □□□□□□□□□ □□□□□□□□□ □□□□ □□□□□□□□□□□□ □□□□□□□□□□□□□□□ □ □□□□□□□□□□□□□□□□ □□□□□. □□□□□□□ DAC SFP+ 10G □□ Digitus® □□□□ (10,21 □□□□□/□), □□□□□□□□□□□□□ 10G (10,52 □□□□□/□), □□□□□□□□□□□□□ 8G (8,5 □□□□□/□), □□□□□□□□□□□□□□□ 4G (4,25 □□□□□/□), □□□□□□□□□□□□□ 2G (2,125 □□□□□/□), □□□□□□□□□ Gigabit-Ethernet (1,25 □□□□□/□), □□□□□□ CPRI 2,3,5,6,7,8, 2 □□□□□□□□□□□□ OBSAI RP3, 4 □□□□□□□□□□□□□ RP3, 8 □□□□□□□□□□□□□□□ RP. □□□□□□□ DAC SFP+ 10G □□□□□□□□□□□□ □ □□□□□□□□□□□□□□□□ □□□□□ □□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□.

□□□□□□□□□□□□ □□□□ □□□□□□□ □□□□□□□□□□□□

- □□□□□□□□□□□□□□□□□ □□□□□□□ AWG 30
- □□□□□□□□□□□□□□□ □□□□□□□□□□: 0,5 □
- □□□□□□□□□□□□□□□□□ □□□□□□□□□ □□□□□□□□□ □□□□□□□: 1,0625-10,52 □□□□□/□
- □□□□□□□□□□□□□□□□□ □□□□□ □□□□□□□□□□□□: Ethernet 10G (10,21 □□□□□/□), □□□□□□□□□□□□□ 10G (10,52 □□□□□/□), □□□□□□□□□□□□□ 8G (8,5 □□□□□/□), □□□□□□□□□□□□□□□ 4G (4,25 □□□□□/□), □□□□□□□□□□□□□ 2G (2,125 □□□□□/□), □□□□□□□□□□□□□□□ 1G (1,0625 □□□□□/□), Gigabit-Ethernet (1,25 □□□□□/□), □□□□□□ CPRI 2,3,5,6,7,8, 2 □□□□□□□□□□□□ OBSAI RP3, 4 □□□□□□□□□□□□ RP3, 8 □□□□□□□□□□□□□□□ RP
- □□□□□□□□□□ □ □□□□□□□□□□□□□□□ □□□□□□□□□□ □□□□□□□□□□□□□□□□□: Allnet, CISCO, D-Link, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL

- □□□□□□□□□□ DDM / DOM
- □□□□□□□□□□ □□□□□□□□□□□□□: □□ 0 □□ 70 °C
- □□□□□□□□□: SFP+
- □□□□□□□□□□□□: +3,3 □ (□□□□□□□□□)
- □□□□□□□□□□□□□□□□ □□□□□□□□□□: 0,5 □□
- □□□□ □□□□□□□□□□□□□□: DAC

Attributes

- AWG: 30
- Length: 0.5 m
- DDM Support: yes
- Manufacturer compatibility: Universal (MSA)
- Connection: SFP+
- Ethernet speed: 10 Gigabit

Package contents

- □□□□□□□ DAC SFP+ 10G 0,5 □
- □□□□□□□□ □□□□□□□□□□□□□□□ □□□□□□□□□□□□□□

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	2.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.01	26.00	26.00	2.00	1,352.00
Packaging Unit Single	1	0.01	26.00	26.00	2.00	1,352.00
Net single without Packaging	1	0.10	5.80	1.40	1.10	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:







Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com