

DIGITUS® DAC SFP+ 10G 0,5 m

DN-81220

EAN 4016032445937



10G SFP+ DAC Cable 0.5m, AWG 30 Allnet, CISCO, Dell, D-Link, Edimax, Etherwan, Fortinet,

Das DAC SFP+ 10G von Digitus® ist ein hochwertiges, passives Kabel für die Verbindung von SFP+ Ports. Es ist kompatibel mit DAC SFP+ 10G von Digitus® (10,21 mm/Ø), 10G (10,52 mm/Ø), 8G (8,5 mm/Ø), 4G (4,75 mm/Ø), 2G (2,125 mm/Ø), Gigabit-Ethernet (1,25 mm/Ø), CPR1 2,3,5,6,7,8, 2 OBSAI RP3, 4 OBSAI RP3, 8 OBSAI RP. Das DAC SFP+ 10G ist ein hochwertiges, passives Kabel für die Verbindung von SFP+ Ports.

Technische Eigenschaften

- Drahtstärke: AWG 30
- Kabellänge: 0,5 m
- Drahtquerschnitt: 1,0625-10,52 mm²/Ø
- Kompatibilität: Ethernet 10G (10,21 mm/Ø), Ethernet 10G (10,52 mm/Ø), Ethernet 8G (8,5 mm/Ø), Ethernet 4G (4,75 mm/Ø), Ethernet 2G (2,125 mm/Ø), Gigabit-Ethernet (1,25 mm/Ø), OBSAI RP3, 4 OBSAI RP3, 8 OBSAI RP
- Kompatibilität: Allnet, CISCO, Dell, D-Link, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL

- DDM / DOM
- Temperaturbereich: 0 bis 70 °C

Attributes

- AWG: 30
- Length: 0.5 m
- DDM Support: yes
- Manufacturer compatibility: Universal (MSA)
- Connection: SFP+
- Ethernet speed: 10 Gigabit

Package Contents

- 1x DAC SFP+ 10G 0,5 m
- 1x Verpackungseinheit

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	2.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.01	26.00	26.00	2.00	1,352.00
Packaging Unit Single	1	0.01	26.00	26.00	2.00	1,352.00
Net single without Packaging	1	0.10	5.80	1.40	1.10	0.00

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com