

DN-81224

EAN 4016032445975



Allnet,CISCO,Dell,D-Link,Edimax,Etherwan,Fortinet,

DAC SFP+ 10G 2 Digitus® 10G (10,52 Gbit/s), 8G (8,5 Gbit/s), 4G (4,25 Gbit/s), 2G (2,125 Gbit/s), Gigabit-Ethernet (1,25 Gbit/s), CPRI 2,3,5,6,7,8, 2 OBSAI RP3, 4 RP5, 8 RP. DAC SFP+ 10G 2 Digitus® 10G (10,52 Gbit/s), 8G (8,5 Gbit/s), 4G (4,25 Gbit/s), 2G (2,125 Gbit/s), Gigabit-Ethernet (1,25 Gbit/s), CPRI 2,3,5,6,7,8, 2 OBSAI RP3, 4 RP5, 8 RP. DAC

XX

- 000000000000000000000000 AWG 24
- 000000000000000000000000: 5 0
- 00000000000000000000000000000000: 1,0625-10,52 0000/0
- 00000000000000000000000000000000: Ethernet 10G (10,21 0000/0), 0000
(2,125 0000/0), 0000000000000000 IG (1,0625 0000/0), Gigabit-Ethernet (1,25 0000/0)
- OBSAI RP3, 4 0000000000000000 RP3, 8 0000000000000000 RP
- 000: Allnet, C
ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM,
JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL

- 00000000 DDM / DOM
- 00000000 00000000: 00 0 00 70 °C

1. 000000000000: SFP+
 2. 000000000000: DAC SFP+ 10G 000000000000. 00000000 DAC SFP+ 10G 00 Digitus® 00000000
 3. 000000000000: 2G (000000000000). 000000000000 2G (2,125 000000/0), 000000000000
 4. 000000000000: RP3, 4 000000000000 RP5, 8 000000000000 RP. 00000000
 5. 000000000000: DAC

Attributes

- AWG: 24
- Length: 5 m
- DDM Support: yes
- Manufacturer compatibility: Universal (MSA)
- Connection: TOG 100 S2 BNC/d, 28mm BNC
- Ethernet speed: 10 Gigabit

Package Contents

- [illegible]

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	7.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.15	32.00	32.00	4.00	4,096.00
Packaging Unit Single	1	0.15	32.00	32.00	4.00	4,096.00
Net single without Packaging	1	0.26	5.80	1.40	1.10	0.00

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com