DIGITUS® ☒☒☒☒☒☒ DAC SFP+ 10G 5 ☒

DN-81224
EAN 4016032445975

SFP+ 10G DAC Cable 5m, AWG 24
Allnet,CISCO,Dell,D-Link,Edimax,Etherwan,Fortinet,

☒☒☒☒☒☒ DAC SFP+ 10G ☒☒ Digitus® ☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒ ☒☒☒ ☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒☒☒ ☒ ☒☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒. ☒☒☒☒☒☒ DAC SFP+ 10G ☒☒ Digitus® ☒☒☒☒
(10,21 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 10G (10,52 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 8G (8,5 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 4G (4,25 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 2G (2,125 ☒☒☒☒/☒), ☒☒☒☒☒☒☒
Gigabit-Ethernet (1,25 ☒☒☒☒/☒), ☒☒☒☒☒ CPRI 2,3,5,6,7,8, 2 ☒☒☒☒☒☒☒☒☒☒ OBSAI RP3, 4 ☒☒☒☒☒☒☒☒☒☒ RP3, 8 ☒☒☒☒☒☒☒☒☒☒☒ RP. ☒☒☒☒☒☒ DAC SFP+ 10G ☒☒☒☒☒☒☒☒☒☒ ☒ ☒☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒☒☒☒☒☒.

☒☒☒☒☒☒☒☒☒☒ ☒☒☒ ☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒

- ☒☒☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒ AWG 24
- ☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒: 5 ☒
- ☒☒☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒: 1,0625-10,52 ☒☒☒☒/☒
- ☒☒☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒: Ethernet 10G (10,21 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 10G (10,52 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 8G (8,5 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 4G (4
(2,125 ☒☒☒☒/☒), ☒☒☒☒☒☒☒☒☒☒☒ 1G (1,0625 ☒☒☒☒/☒), Gigabit-Ethernet (1,25 ☒☒☒☒/☒), ☒☒☒☒☒ CPRI 2,3,5,6,7,8, 2 ☒☒☒☒☒☒☒☒☒☒ OBSAI RP3, 4 ☒☒☒☒☒☒☒☒☒☒ RP3, 8 ☒☒☒☒☒☒☒☒☒☒☒ RP
- ☒☒☒☒☒☒☒☒☒ ☒ ☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒☒☒☒☒: Allnet, CISCO, 3COM, D-LINK, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL
- ☒☒☒☒☒☒☒☒☒ DDM / DOM
- ☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒: ☒☒ 0 ☒☒ 70 °C
- ☒☒☒☒☒☒☒☒: SFP+
- ☒☒☒☒☒☒☒☒☒☒☒: +3,3 ☒ (☒☒☒☒☒☒☒☒)
- ☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒: 0,5 ☒☒
- ☒☒☒ ☒☒☒☒☒☒☒☒☒☒☒: DAC

Attributes

- AWG: 24
- Length: 5 m
- DDM Support: yes
- Manufacturer compatibility: Universal (MSA)
- Connection: SFP+
- Ethernet speed: 10 Gigabit

Package contents

- ☒☒☒☒☒☒ DAC SFP+ 10G 5 ☒
- ☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒☒☒ ☒☒☒☒☒☒☒☒☒☒

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	7.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.15	32.00	32.00	4.00	4,096.00
Packaging Unit Single	1	0.15	32.00	32.00	4.00	4,096.00
Net single without Packaging	1	0.26	5.80	1.40	1.10	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:

21
22
23
24
SFP2
Console

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com