# DIGITUS® □□□□□□ DAC SFP+ 10G 2 □

**DN-81222-02**

**EAN 4016032446095**

**SFP+ 10G DAC Cable 2m AWG 30, HP compatible**

Кабели DAC SFP+ 10G от Digitus® идеально подходят для соединения коммутаторов в магистральной сети . Кабели DAC SFP+ 10G от Digitus® подд (10,21 Гбит /с ), оптоволокно 10G (10,52 Гбит /с ), оптоволокно 8G (8,5 Гбит /с ), оптоволокно 4G (4,25 Гбит /с ), оптоволокно 2G (2,125 Гбит /с ), оптовол Gigabit-Ethernet (1,25 Гбит /с ), опции CPRI 2,3,5,6,7,8, 2 интерфейса OBSAI RP3, 4 интерфейса RP3, 8 интерфейсов RP. Кабели DAC SFP+ 10G совместимы с коммутаторами Hewlett Packard (HP) H3C.

Удлинитель для медных соединений

- Твинаксиальный кабель AWG 30
- Максимальное удаление : 2 м
- Поддерживаемая скорость передачи данных : 1,0625-10,52 Гбит /с
- Поддерживаемые виды применения : Ethernet 10G (10,21 Гбит /с ), оптоволокно 10G (10,52 Гбит /с ), оптоволокно 8G (8,5 Гбит /с ), оптоволокно 4G (4 (2,125 Гбит /с ), оптоволокно 1G (1,0625 Гбит /с ), Gigabit-Ethernet (1,25 Гбит /с ), опции CPRI 2,3,5,6,7,8, 2 интерфейса OBSAI RP3, 4 интерфейса RP3, 8 интерфейсов RP
- Совместимые марки : совместимость с Hewlett Packard (HP/Aruba)
- Поддержка DDM / DOM
- Диапазон температур : от 0 до 70 °C
- Разъемы : SFP+
- Напряжение : 3,3 В (питание )
- Потребляемая мощность : 0,5 Вт
- Тип трансивера : DAC
- Connection: SFP+
- Manufacturer compatibility: HP
- Ethernet speed: 10 Gigabit

**Attributes**

- AWG: 30
- Mode: Copper
- Length: 2 m
- DDM Support: yes

**Package contents**

- Кабель DAC SFP+ 10G 2 м
- Краткое практическое руководство

**Logistics**

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|---|---|---|---|---|---|---|
| **Packaging Unit Carton** | 120 | 1.50 | 48.00 | 48.00 | 38.00 | 87,552.00 |
| **Packaging Unit Inside** | 1 | 0.01 | 26.00 | 26.00 | 3.00 | 2,028.00 |
| **Packaging Unit Single** | 1 | 0.01 | 26.00 | 26.00 | 3.00 | 2,028.00 |
| **Net single without Packaging** | 1 | 0.02 | 5.80 | 1.40 | 1.10 | 0.00 |

**Safety notes**

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.

- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com