

DIGITUS® DisplayPort

AK-340106-010-S
EAN 4016032450320



DisplayPort connection cable, DP M/M, 1.0m,w/lock, UHD 8K, Vers. 1.3/1.4, bl

Digitus DisplayPort connection cable, DP M/M, 1.0m,w/lock, UHD 8K, Vers. 1.3/1.4, bl. This cable is designed for high-resolution video and audio transmission. It is compatible with a wide range of devices, including CAD/CAM, GIS, 3D, and 4K/8K displays. The cable features a locking mechanism for secure connections and is made of high-quality materials for durability.

- Cable length: 32,4 cm
- Resolution: 8K@60 Hz (Ultra HD)
- Resolution: 7680 x 4320 dpi; 5120 x 2880 dpi; 3840 x 2160 dpi
- Color: 24 bit RGB
- Channels: 1-8
- Resolution: 32-192 Hz
- HDCP & DPCP
- Plug&Play

- AWG: 30
- Color cable: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- DisplayPort standard: DisplayPort 1.4
- Ferrite filter: none
- HDTV Standard: Ultra HD 8K
- Hoods: molded
- Interlock: Snap fastener
- Resolution max.: 7680 x 4320 Pixel, 60Hz
- Length: 1 m
- AOC - Active Optical Cable: no
- Shielding: single shielding

Attributes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	8.00	50.00	33.00	22.00	36,300.00
Packaging Unit Inside	5	0.40	15.00	8.00	22.00	2,640.00
Packaging Unit Single	1	0.08	12.00	1.50	14.50	261.00
Net single without Packaging	1	0.06	14.00	12.50	2.00	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com