

DIGITUS USB Type-C adapter / converter, Type-C™ to USB Type-C + 3.5mm stereo

AK-300400-002-S
EAN 4016032451105



USB Type-C Splitter cable, type C - 3.5mm+type C M/F/F, 0.2m, Gen2, 5A, 10GB, Vers. 3.1, bl

This adapter / converter allows you to connect headphones, a headset or speakers to a device with a USB Type-C socket as well as to extend your USB Type-C interface at your Smartphone, Tablet, Notebook.

Phone calls or listen to music while charging your device.

- Power supply up to 20V/5A and 100W
- Support of PD 3.0 fast charging (Power Delivery)
- Support of 24bit / 192 KHz digital music
- Plug and Play Installation
- USB Type-C signal pass through (Data and Power)
- USB Type-C connector can be used in both directions
- No support of phone function

- System requirements: Win7, Win8, Win10 + higher

Attributes

- AWG: 24
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB-C jack
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 0.2 m
- Shielding: single shielding
- USB-C Products: yes

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	4.80	40.00	30.00	18.00	21,600.00
Packaging Unit Inside	10	0.24	36.00	28.00	9.60	9,676.80
Packaging Unit Single	1	0.02	19.60	9.20	1.05	189.34
Net single without Packaging	1	0.00	16.00	4.40	1.10	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com