

# Digitus® USB Type-C Gen2 extension cable, Type-C to C

AK-300210-007-S

EAN 4016032451129



## USB Type-C extension cable, type C M/F, 0.7m, Gen2, 5A, 10GB, 3.1 Version, bl

This USB Type-C extension cable allows to extend the usage distance of the type C interface at the Notebook, Tablet, Smartphone or at the docking station.

### Extend your original Type C port on your MacBook or other device to a suitable location

- USB 3.1 data transfer rate up to 10 Gbps, Superspeed+
- Power supply support up to 20V/5A, 100W
- Support of USB PD (Power Delivery) specification
- Support for Video/Audio up to 4K (4096x2304, 30fps)
- Support of DisplayPort Video/Audio signals

### Attributes

- AWG: 26
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB-C jack
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 3.0 / 3.1
- Length: 0.7 m
- Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
<b>Packaging Unit Carton</b>	200	5.90	35.00	26.00	24.00	21,840.00
<b>Packaging Unit Inside</b>	10	0.30	25.00	30.00	7.60	5,700.00
<b>Packaging Unit Single</b>	1	0.03	1.00	11.50	21.50	247.25
<b>Net single without Packaging</b>	1	0.03	1.00	10.50	9.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com