DIGITUS USB KVM Extender over Cat 5

DS-51201 EAN 4016032451181





KVM Extender USB, 1 Local + 1 Remote User up to 200M(CAT5, UTP), resolution 1920X1080 at 60Hz

The KVM Cat.5 USB Extender Kit is a pair of devices (Transmitter and Receiver) for high-density applications where you want full use of the keyboard, mouse, and monitor, but there is no room for a server nearby.

Move your console to the most convenient place – Enjoy flexibility!

- High resolution video up to 1920x1080 @ 60Hz for distances of up to 200 meters
- High quality resolutions thanks to the built-in video, keyboard and mouse signal enhancement

 Dual console operation - Control your system from both the local and remote unit

1

- Supports keyboard/mouse connection of USB interface to computer at local side
- DDC2B support for remote monitor
- No software or driver installation required
- Supports BIOS level operation
- Device Power consmption (Max.): 12.2W
- DC plug Size: 5.5x2.1x10mm

Package contents

- 1x local unit
- 1x remote unit
- 1 x Manual
- 2x power adaptor DC 12V

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	14.00	38.00	41.50	47.50	74,907.50
Packaging Unit Inside	1	0.70	7.50	23.00	17.00	2,932.50
Packaging Unit Single	1	0.70	7.50	23.00	17.00	2,932.50
Net single without Packaging	1	0.40	2.60	7.20	9.70	0.00

More images:













Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- · For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com