

# DIGITUS USB Type-C™ 4K HDMI Graphics Adapter + USB-C™ (PD)

DA-70856

EAN 4016032451495



## USB Type C to HDMI Adapter, 4K/60Hz + USB C (PD), black

The USB Type-C™ 4K HDMI graphics adapter allows you to connect a TV set, monitor or projector to a USB-C™ device. The highest possible resolution is UHD (4K/60Hz). In addition, it has another USB-C™ port with Power Delivery (PD) 2.0 functionality to power your mobile device while using the adapter. It is suitable for all operating systems: Windows, Mac, Google Chrome. The adapter is a must-have accessory, whether you use it privately when connecting your laptop to a TV set or professionally for presentations with an HDMI projector.

**Enables the connection of a monitor, TV or projector with an HDMI port to your USB-C™ device and allows you to charge it at the same time**

- Connection 1: USB-C™ plug
- Connection 2: HDMI socket
- Connection 3: USB-C™ socket
- Extends your USB-C™ device with an HDMI port
- Provides an USB-C™ port with Power Delivery (PD) 2.0 to charge your mobile device
- 1x HDMI (UHD, 4K/60Hz)
- 1x USB-C™ (PD 2.0, max. 60W)
- Supports Ultra HD (4K/60Hz)
- USB-C™ version: USB 3.1 (Gen. 1)
- Corresponds to the VESA DisplayPort Alternate Mode
- Chipset: VL100 / PS1716
- Supports HDCP 2.2
- Cable length: 11.0 cm

- Color: Black
- Dimensions: L 18.0 x W 4.0 x H 1.2 cm
- Weight: 20 g
- Not all USB-C™ ports support all functions of USB Type-C™ standards. Make sure that the USB-C™ port of your laptop supports the DisplayPort Alternate Mode (DP Alt-mode).
- The video output capability depends on the graphics card of your laptop and the connected monitor. Some screens also have a limited resolution.

## Attributes

- HDTV Resolution max.: 4096 x 2160 Pixel, 60Hz
- Housing: Aluminum
- LAN connector (RJ45): no
- Card reader: no
- Number of audio ports: 0
- Number of display ports: 2
- Number of network ports: 0
- Number of USB A ports: 0
- Number of USB-C ports: 1
- Number of video ports: 2
- USB-C Products: yes
- Video connection ports: HDMI

## Package contents

- USB Type-C™ 4K HDMI Graphics Adapter + USB-C™ (PD)
- QIG (quick installation guide)

| Logistics                    |              |             |            |            |             |           |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
| Packaging Unit Carton        | 80           | 8.00        | 50.00      | 34.00      | 30.00       | 51,000.00 |
| Packaging Unit Inside        | 1            | 0.10        | 23.50      | 7.50       | 2.30        | 405.38    |
| Packaging Unit Single        | 1            | 0.10        | 23.50      | 7.50       | 2.30        | 405.38    |
| Net single without Packaging | 1            | 0.03        | 5.80       | 4.00       | 1.50        | 0.00      |

**More images:**



**Safety notes**

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)