

# DIGITUS® HDMI Ultra High Speed Connection Cable

AK-330124-010-S  
 EAN 4016032454298



HDMI Ultra High Speed connection cable, type A M/M, 1.0m, w/Ethernet, UHD 8K 60p, gold, bl

Digitus HDMI Ultra High Speed connection cable, type A M/M, 1.0m, w/Ethernet, UHD 8K 60p, gold, bl. This cable is designed for high-speed data transfer and is compatible with HDMI 2.1, 2.0, 1.4, and 1.3. It features a gold-plated connector surface and a double-shielded design to reduce electromagnetic interference (EMI). The cable is made of high-quality PVC material and is suitable for use in various environments. It is a 1.0m long cable with a type A M/M connector. The cable is compatible with HDMI 2.1, 2.0, 1.4, and 1.3. It features a gold-plated connector surface and a double-shielded design to reduce electromagnetic interference (EMI). The cable is made of high-quality PVC material and is suitable for use in various environments. It is a 1.0m long cable with a type A M/M connector.

- Supports 8K 60p
- Supports 4K 3D 50/60p
- Supports 14 x 16
- HDR (High Dynamic Range)
- ARC (Audio Return Channel)
- Lip-Sync
- Dolby TrueHD
- 21:9
- 32

- Ethernet (HEC)

**Attributes**

- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, plug
- Connector surface: gold-plated
- Ferrite filter: none
- HDMI Standard: Ultra High Speed HDMI
- HDTV Standard: Ultra HD 8K
- Hoods: Metallic housing
- Resolution max.: 7680 x 4320 Pixel, 60Hz
- Length: 1 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	9.20	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	0.92	28.00	36.00	25.00	25,200.00
Packaging Unit Single	1	0.09	16.00	3.00	14.00	672.00
Net single without Packaging	1	0.09	14.00	3.00	13.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)