

# DIGITUS® Comutador de rede Gigabit Ethernet de 5 portas, industrial, não gerido

DN-651107

EAN 4016032454472



## Comutador Ethernet Gigabit industrial 5 portas, calha DIN, gama de temperaturas alargada

O Interruptor Gigabit Industrial DIGITUS® foi concebido para ambientes agressivos onde estão expostos à humidade, flutuações de temperatura e vibrações. Com uma gama de temperaturas de -40°C a 75°C, o Comutador Gigabit Industrial pode ser utilizado nas condições mais adversas. A disponibilidade constante é garantida em áreas altamente sensíveis, como os transportes, a produção, o tráfego e a vigilância de segurança. Graças ao sistema simples plug-and-play, o Industrial Gigabit Switch pode ser rapidamente integrado no respetivo ambiente. A conectividade Gigabit faz do Industrial Gigabit Switch uma solução flexível e económica para ambientes industriais.

### Montagem dupla em calha standard / superior

- 5 x 10/100/1000Base-TX portas Ethernet
- Detecção automática de cabos - Função Auto MDI / MDI-X
- Normas suportadas: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab Gigabit Ethernet
- Controlo de fluxo e contrapressão IEEE802.3x
- Tecnologia store-and-forward para uma transferência de dados otimizada
- Detecção/definição automática de velocidade e half/full duplex
- Placa traseira com 10Gbps
- Suporta até 8K endereços MAC
- Caixa metálica compacta e robusta
- Excelente proteção contra curto-circuitos

- Proteção contra raios e sobretensões
- Fonte de alimentação redundante: DC 12 -56V / 18-36V AC, fonte de alimentação redundante com função de proteção contra inversão de polaridade
- Gama de temperaturas de funcionamento alargada, -40 °C ~ +75 °C
- Ligação de terminal amovível
- Consumo de energia: 2,76 W
- MTBF: 500.000 horas
- EN 50155 (EN 60068-2-6) Vibração
- EN 50155 (EN 60068-2-27) Choque
- EN 50155 (EN 60068-2-32) Queda livre

### Attributes

- Number of ports: 5
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: no

### Package contents

- Comutador Gigabit industrial de 5 portas
- Guia de início rápido

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	16	7.40	35.00	24.00	56.00	47,040.00
Packaging Unit Inside	1	0.46	16.20	21.10	6.40	2,187.65
Packaging Unit Single	1	0.46	16.50	6.50	21.50	2,305.88
Net single without Packaging	1	0.16	8.20	3.20	10.40	0.00

**Safety notes**

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
  - The mains cable, power supply unit or plug for the power supply is damaged or worn;
  - Liquid has penetrated the appliance;
  - The device has been exposed to rain or water;
  - The device has been dropped or the housing has been damaged;
  - The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)