

DIGITUS® Módulo SFP de cobre de 1,25 Gbps, RJ45

DN-81005-01

EAN 4016032454915



Módulo SFP de cobre de 1,25 Gbps, RJ45, compatível com HP 10/100/1000Base-T, até 100 metros

Os módulos transceptores DIGITUS® Mini GBIC (SFP) oferecem a mais elevada qualidade e fiabilidade. O módulo oferece a oportunidade perfeita para expandir o seu computador de rede Gigabit com uma porta de ligação ascendente SFP gratuita através de uma ligação RJ45 adicional. Graças à sua capacidade de "hot-plug", pode instalar o módulo sem interromper o tráfego de rede ou reiniciar o dispositivo. A conformidade com a norma MSA (Multi Source Agreement) também garante a compatibilidade com os fabricantes de computadores de rede mais comuns.

A extensão plug and play para o seu switch de rede

- Módulo Mini GBIC SFP (Small Form Factor Pluggable)
- Compatível com os seguintes fabricantes: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Débito máximo de dados bidirecional até 1,25 Gbps
- Em conformidade com a norma IEEE 802.3z Gigabit

- Alta qualidade e máxima fiabilidade
- Fácil instalação plug and play
- Compatível com MSA (Multi Source Agreement)
- Ligação a quente - possibilidade de instalação durante o funcionamento
- Auto MDI/MDI-X
- Ligação: 1x RJ45, CAT 5
- Distância: até 100 m
- Temperatura de funcionamento: 0 °C ~ 70 °C

Attributes

- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: HP, Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- Módulo SFP

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.20	1.50	1.50	7.00	0.00

More images:



SFP Modules							
Product Number	MM Code	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Version
DM-0101	42100000040	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0102	42100000070	1.0 Gbps	10 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0104	42100000070	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0105	42100000080	1.0 Gbps	100 m	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0106	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0108	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0109	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0110	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0111	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0112	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0113	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0114	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0115	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0116	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0117	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0118	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0119	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	
DM-0120	42100000080	1.0 Gbps	20 km	LC Duplex Duplex	191mm	0 to +70 °C	

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com