DIGITUS® USB-C connection cable, USB-A - USB-C

AK-300154-010-S

EAN 4016032455233



USB Type-C connection cable, type USB-A to USB-C M/M, 1.0m, 5V3A, 15W, 480MB, 2.0 Version, bl

For connecting external USB end devices (with C socket, e.g. tablet, notebook or smartphone) to the USB host (e.g. PC or notebook). Transfer rate up to 480 Mbps (high-speed).

For super-fast synchronization and charging

- Fast USB 2.0 data transfer with up to 480 Mbps
- Supports up to 5V3A, 15W power supply
- Supports the USB PD (Power delivery) specification.
- USB Type-C plug can be used on both sides

Attributes

- AWG: 22
- Feritni filtar: nema
- Kabel u boji: crni
- Konektor 1: USB A, utikač
- Konektor 2: USB C, utikač
- Površina konektora: poniklano
- USB sukladnost: USB 2,0
- Duljina: 1 m
- oklop: bez oklopa
- USB-C proizvodi: Da

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	300	11.30	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	0.38	28.00	19.00	6.00	3,192.00
Packaging Unit Single	1	0.04	25.00	14.00	0.60	210.00
Net single without Packaging	1	0.03	14.00	11.00	0.50	0.00

More images:







Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.







Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com