DIGITUS® USB-C connection cable, USB-C - USB-C

AK-300138-030-S

EAN 4016032455998



USB Type-C connection cable, Type-C - C M/M, 3.0m, 5V/3A 15W, 480Mbps, Version 2.0, bl

For connecting external USB-C devices (e.g. tablet or smartphone) to the USB-C host (e.g. PC, notebook or USB hub). Data transfer rate up to 480 Mbps (high-speed).

For super-fast synchronization and charging

- Copper cores, foil and braid shielded for robustness and a reliable connection
- Data transfer rate up to 480 Mbps (High-speed).
- Power supply up to 5V/3A 15W, 480MB
- Supports the USB PD (Power delivery) specification
- Type C plug can be used on both sides

Attributes

- AWG: 22
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 2.0
- Length: 3 m
- Shielding: Double shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	10.30	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	1.03	20.00	8.00	24.00	3,840.00
Packaging Unit Single	1	0.10	15.00	1.00	17.00	255.00
Net single without Packaging	1	0.09	16.00	15.00	1.00	0.00


Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:











Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com