

DIGITUS® Caixa de emenda de fibra ótica com fecho de libertação rápida, extensível

DN-96200-QL

EAN 4016032458210



Caixa de emenda de fibra ótica, 1U, fecho de libertação rápida, vazia sem painel frontal, buçim M20/M25, cinzento

A robusta caixa vazia é a base para a montagem de uma caixa de junção personalizada. Para além das caixas de junção pré-montadas da DIGITUS®, tem a possibilidade de montar você mesmo os componentes necessários. Utilize a nossa extensa gama de painéis frontais, acopladores e pigtaills. Os nossos produtos são submetidos a um controlo de qualidade constante e estão sujeitos às normas e padrões internacionais aplicáveis na cablagem de fibra ótica. Isto permite-nos garantir um desempenho ótimo e a melhor qualidade para a sua rede. O painel frontal pode ser facilmente instalado com o material de montagem incluído. O novo sistema de libertação rápida torna a instalação mais fácil do que nunca.

Padrões orientados para o futuro e qualidade de topo de gama para a sua rede.

- Dimensões internas aprox. (A x L x P): 44 x 428 x 240 mm

Attributes

- Assembly: Empty housing
- Color: light grey, RAL 7035
- Type: sliding

Package contents

- 1x caixa de emenda
- 1x saco plástico com buçins M20/M25, abraçadeiras, cliques para cabos, cliques de encaixe, parafusos

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	5	10.50	53.50	33.00	29.00	51,199.50
Packaging Unit Inside	1	2.10	28.00	51.50	5.00	7,210.00
Packaging Unit Single	1	2.10	28.00	51.50	5.00	7,210.00
Net single without Packaging	1	2.10	24.00	48.30	4.40	0.00

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com