

DIGITUS® Cabo QSFP+ 40G 10m AOC

DN-81313

EAN 4016032460121



Cabo QSFP+ 40G 10m AOC Allnet, CISCO, Dell, D-Link, Edimax, Etherwan, Fortinet,

Os cabos activos DIGITUS® 40G QSFP+ AOC são uma solução de interconexão de curto alcance de alto desempenho e baixo consumo de energia que suporta InfiniBand QDR/DDR/SDR, 12,5G/10G/8G/8G/4G/4G/2G canal de fibra, PCIe e SAS. Estão em conformidade com o QSFP MSA e o IEEE P802.3ba. São utilizados quatro canais full duplex, sendo cada canal capaz de transferir dados a velocidades até 11,3 Gb/s, o que dá uma taxa agregada de 45,2 Gb/s. Os cabos activos DIGITUS® 40G QSFP+ AOC oferecem uma maior densidade de portas e economia de custos no sistema global.

Largura de banda elevada sem atrasos ou perda de sinal

- 10 m de distância máxima
- Taxa de dados suportada de 2,125-41,2 Gbps
- Aplicações suportadas: 12,5G Fibre Channel, 10G Fibre Channel, 8G Fibre Channel, 4G Fibre Channel e 2G Fibre Channel
- Marcas compatíveis: Allnet, CISCO, 3COM, D-LINK, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL

- Suporte DDM / DOM
- Gama de temperaturas: 0-70 °C
- Conexões: QSFP
- Alimentação: + 3,3V tensão de alimentação
- Consumo de energia: <1,5W
- Fibra multimodo com comprimento de onda de 850nm

Attributes

- Length: 10 m
- Wavelength: 850 nm
- DDM Support: yes
- Manufacturer compatibility: Cisco
- Connection: QSFP+
- Ethernet speed: 40 Gigabit

Package contents

- Cabo QSFP+ 40G 10m AOC
- Guia de início rápido

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	150	1.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.01	26.00	26.00	2.00	1,352.00
Packaging Unit Single	1	0.01	26.00	26.00	2.00	1,352.00
Net single without Packaging	1	0.19	11.00	1.80	1.30	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage

- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com