DIGITUS® 3-in-1 USB charging cable, 0.15m

DB-300160-002-S

EAN 4016032466208



USB charger cable, 0.15m 3-in-1 cable, nylon braid, black

The DIGITUS® 3-in-1 charging cable is ideal for charging your portable devices on a power supply unit, PC or other device with a USB-A connection. Use one cable to charge all your devices. The compact dimensions make the cable the ideal companion for home, office or when traveling.

3-in-1 multi-charging cable for connecting devices with USB-C, micro USB or 8-pin connection to a USB-A connection

- Supported charging power: 10 W (5 V / 2 A)
- Operating temperature: -10 ~ 50°C
- Operating humidity: 0 - 75%
- Connection 1: USB-A, plug
- Connection 2: Apple, plug/⊟Micro-USB, plug/⊟USB-C, plug

Attributes

- AWG: 30
- Color cable: black
- Connector 1: USB A, plug
- Connector surface: nickel-plated
- Hoods: Metallic housing
- Wire material: CU
- Length: 0.15 m
- Shielding: Unshielded
- USB-C Products: yes

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	7.50	29.00	55.00	20.00	31,900.00
Packaging Unit Inside	10	1.88	26.50	27.50	9.00	6,558.75
Packaging Unit Single	1	0.19	5.50	23.50	2.00	258.50
Net single without Packaging	1	0.02	46.80	15.00	0.30	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:








Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com