

# DIGITUS® Active DisplayPort Adapter / Converter, DP to HDMI

DB-340415-002-S  
EAN 4016032468752



**DisplayPort Adapter Cable, Type DP - HDMI A M/F, 0.2m, w/lock, UHD 4K, HDMI 2.0, act, gold, bl**

The 4K DisplayPort to HDMI Adapter / Converter (DisplayPort plug to HDMI jack) enables you to reproduce content from your computer or notebook directly onto your TV or other HDMI displays. It supports a UHD resolution of up to 4096 x 2160p. Your images, videos, documents, presentations etc. can be displayed in Ultra HD and optimally presented during meetings or for private use.

**Converts DisplayPort signals to HDMI signals in resolutions of up to UHD 4K**

**Attributes**

- AWG: 32
- Color cable: black

- Connector 1: DP, plug
- Connector 2: HDMI type A, jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Resolution max.: 4096 x 2160 Pixel, 30Hz
- Length: 0.2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

**Package contents**

- 1 x Active DisplayPort Adapter / Converter, DP to HDMI

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 80           | 7.70        | 52.00      | 29.00      | 39.00       | 58,812.00       |
| Packaging Unit Inside        | 20           | 1.93        | 27.00      | 25.00      | 17.00       | 11,475.00       |
| Packaging Unit Single        | 1            | 0.10        | 23.50      | 7.50       | 2.30        | 405.38          |
| Net single without Packaging | 1            | 0.09        | 2.50       | 4.50       | 1.50        | 0.00            |

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)